



NEW! testo 330-2LL combustion analyzer with graphic display

Technical Data

Parameter	Measuring Range	Accuracy
O ₂ Long Life Sensor	0 to 21 Vol.%	±0.2 Vol.%
CO Long Life Sensor (H ₂ compensated)	0 to 8,000 ppm	±10 ppm or ±10% rdg. ±20 ppm or ±5% of rdg. ±10% of rdg.
Auto CO dilution	8,000 to 30,000 ppm	
NO	0 to 3,000 ppm	±5 ppm ±5% of rdg. ±10% of rdg.
CO (low meas.)	0 to 500 ppm	±2 ppm ±5% of rdg.
Draft and pressure	-4 to 16" H ₂ O 0 to 80" H ₂ O	±0.2" H ₂ O ±1% of rdg. 1.5% of rdg.
CO ₂ (calculated)	0 to CO ₂ max	
Temperature	-40 to 1832 °F	
Efficiency	0 to 100%	

Specifications

Description	
Operating temp range	23 to 113°F
Storage/transport range	-4 to 122°F
Power supply	lithium ion rechargeable, AC 6.3V/1.2A
Dimensions	10" x 3.5" x 2.5"
Weight	1.5 pounds
Memory	500,000 readings
Display	color graphic (240 x 320 pixels)
Battery charge time	>6 hours

